



AtmoCheck® VA

Gas analysis apparatus for random measurement of O₂ and CO₂

AtmoCheck® VA is a compact laboratory sample analyser for fast, reliable and precise measurement of oxygen and carbon dioxide concentrations in modern food packaging technology.

AtmoCheck® VA is characterised by its simple and intuitive operation, short measuring times and low sample gas consumption. The integrated data logging software supports traceability and complete documentation (HACCP/IFS/ISO) It is therefore the ideal device to use for fast, reliable and exact testing, either directly at the packaging machine, in the warehouse or Quality Assurance laboratory.

The AtmoTool® software provides fast and uncomplicated communication, is safe to use and is equipped with everything required to upgrade from manual handwritten to automatic electronic recording of all measurement data that is easily transferred to your computer.

Fields of application

- ⇒ Quality Assurance
- ⇒ Food Technology
- ⇒ Cutting and Welding
- ⇒ Customised solutions

All highlights at a glance

- ⇒ Simple, intuitive handling
- ⇒ Low volume of sample gas required for measurement
- ⇒ Measuring time < 10 sec.
- ⇒ Large, clear illuminated graphic display
- ⇒ Optional: Display of N₂ concentration
- ⇒ Add and select up to 10 products
- ⇒ Add and select up to 10 users
- ⇒ Access to the calibration facility, product selection and user menu is password protected
- ⇒ All measurements and product data are automatically digitally documented – no need for manual logging
- ⇒ Simple transfer and analysis of measured data
- ⇒ Includes AtmoTool® PC software for easy operation and data management
- ⇒ Alarm and data logger suitably pre-configured for every kind of quality control
- ⇒ Pump profiles are easily adjusted to accommodate different types and sizes of packaging
- ⇒ Built in Data Logger will hold up to 1.000 sets of measurement data
- ⇒ Logged data files can be exported in XLSX or CSV formats
- ⇒ USB port for easy data transfer and battery recharging
- ⇒ Simple cleaning and long service life thanks to robust design
- ⇒ Remote service interface for fast support via TeamViewer®

Accessories



The **AtmoCheck®** VA manual and the current version of the **AtmoTool®** software for fast and uncomplicated communication via download link



USB Cable



40 pcs. self-adhesive sealing tabs



Tube with Luer-Lock connection



Suction needle in protective cartridge



2 pcs. Filter for protection against moisture



Needle holder

Technical Data

Measuring principle	O2 electrochemical measuring cell* / CO2 NDIR sensor**	Temperature	Gas and/or environment: 5 – 40 °C
Measuring range	0-100%; in 0,1% steps	Display	Graphic display with backlight
Measuring time	Approx. 10 sec	Switch off	Automatically after 2 minutes of non-use
Calibration	Simple 2-point calibration	Housing	Stainless Steel
Sampling method	Automatic by needle with integral suction pump	Weight	Approx. 6,5 kg
Memory capacity	Circulating memory for 1000 measured values	Dimensions	(HxWxD) 245 x 270 x 200 mm
Interface	USB-Port	Power supply	230 V AC
Software	AtmoTool® software***		

Manufacturing Accreditations and Standards

CE marked

* estimated service life of O2 sensor in air max. 18 month

** estimated service life of CO2 sensor min. 5 years depending on ambient conditions

*** MS Windows is required to run AtmoTool® software

Further models from our product portfolio

AtmoCheck® ONE and DOUBLE

Hand analyser for control of protective gas packaging (MAP)



AtmoCheck® COVER Gas analyser

for random Measurement of O2 and CO2



AtmoCheck® OPTIC

Optical oxygen analyser for easy sample measurement



AtmoCheck® LEAK TEST

Package Leak Detection System & Seal Integrity Tester

